

PRODUCT INFORMATION

Factory Windhoek: Tel. +264-61-235870/2227773 Fax +264-61247414, email: peralinp@iway.na • Sales Windhoek: Tel. +264 61 227 050 • peralini@mweb.com.na • Sales Swakopmund: Tel. +264 64 462 888 • arust@iway.na • Sales Ongwediva: Tel. +264 65 232 035 • Sales Walvis Bay: Tel. +264 64 220 027

Product: POWDER FILL

Product Code: MXF-2

Features:

- Universal filler for interior and exterior use

Description, Properties and Uses:

POWDER FILL dries to a solid and tough product that can be sanded easily to a smooth surface. This filler does not absorb water or humidity. POWDER FILL is suitable for filling small cracks, holes and other defects. It is also possible to skim uneven surfaces to a smooth finish with POWDER FILL.

PRODUCT DATA

Properties	Data	Units
Resin Type	Combination of mineral compounds	-
Drying Times	Touch dry	minutes.
	Hard dry	hours
Over coating Time	1 depending on thickness	hours
Surface Appearance	Matt white	-
Cleaning Solvent	Water	-
Shelf Life	6 month	month
Available colours	White	-
Unit sizes and weights	20kg, 10kg, 5kg, 2kg, 500g	bag

Application Instructions:

Mix POWDER FILL with water to a lump-free stiff paste. Apply this paste with a skimming blade or scraper within 15-20 minutes after mixing. After drying (hardening) sand to a smooth surface and remove the dust. Apply SEALER (MB-30) over prepared POWDER FILL.

Surface preparation and application:

PLASTER:

Plaster must be dry and solid. Apply POWDER FILL. After drying of filler, sand to smooth surface. Apply SEALER (MB-30) over filler.

PRIMED PLASTER:

It is preferred to fill up holes and blemishes once the walls are primed. This gives better visibility. POWDER FILL can be applied on PVA based wall-primers, but must be sealed with SEALER (MB-30).

EXISTING PAINTED SURFACES:

POWDER FILL can be applied on existing PVA paint coating. For use on eggshell or high gloss enamels sand substrate well to a matt surface. Apply POWDER FILL. After drying of filler, sand to smooth surface. Apply SEALER (MB-30) over filler.

WOOD, FIBREBOARD OR SOFTBOARD;

FLEX FILL (MXRP) is recommended for this application.

NB: For application surfaces, other than above, please contact our sales department (Tel: (061) 22 7050) or the technical department (Tel: (061) 22 7773).

Safety Precautions:

Gloves	X
Mask	X
Goggles	
SWALLOWED	Rinse mouth with water. Give water to drink. Seek medical attention!
EYECONTACT	Rinse eyes with water and seek medical advice!
SKINCONTACT	Immediately wash skin with soap and water!
VENTILATION	Ensure adequate ventilated application area!
SPILLAGES	Prevent run off into drains or waterways.
STORAGE	Keep container tightly closed. Store in cool, dry place out of direct sunlight.
FLAMMABLE	Not flammable.

Always keep product out of reach of children. Do not ingest. Avoid eye contact. Do not ingest.